

RESPONSE TO OFFICE ACTION
S/N 09/773,352
Page 2 of 12

A1 cont *b2 cont*
a first member pivotally coupled to the center shaft; and
a second member pivotally coupled to the center shaft, wherein the first member and the second member are rotatable between a first position proximate the shaft and a second position away from the shaft.

4. (Cancelled) The anchor of claim 1, wherein the first member and the second member are rotatable between a first position proximate the shaft and a second position orthogonal to the shaft.

A2 *pub B1* 12. (Amended) An anchor for providing an attachment point on a building structure, comprising:

a center shaft having an attachment end and a piercing end adapted to pierce through the building structure;

a first member pivotally coupled to the center shaft;

a second member pivotally coupled to the center shaft; and

a collar slidably disposed on the center shaft and movable to a position that clamps the building structure between collar and members.

A3 *pub B1* 19. (Amended) An anchor for providing an attachment point on a building structure, comprising:

a center shaft having a first end and a second end;

a ring disposed on the first end;

a first member pivotally coupled to the center shaft;

a second member pivotally coupled to the center shaft, the first member and the second member are rotatable between a first position proximate the shaft and a second position away from the shaft;

a collar slidably disposed on the center shaft, the collar and the first and second members sandwiching the building structure therebetween when the first and second members are in the second position and the collar is slid away from the ring; and